

PAVEMENT MARKING LEGEND

IDENTIFICATION	TYPE	COLOUR	WIDTH (cm)
1	SOLID	YELLOW	10
2	DOUBLE SOLID	YELLOW	10
3	3-6-3 BROKEN	YELLOW	10
4	SOLID;3-6-3 BROKEN	YELLOW	10
5	SOLID	WHITE	10
6	3-3-3 BROKEN	WHITE	10
7	3-6-3 BROKEN	WHITE	10
8	3-9-3 BROKEN	WHITE	10
9	SOLID	WHITE	20
10	1-1-1 BROKEN	WHITE	20
11	3-3-3 BROKEN	WHITE	20
12	3-3-3 BROKEN	WHITE	30
13	SOLID	WHITE	30
14	SOLID	WHITE	45
15	SOLID	WHITE	60
16	1-1-1 BROKEN	WHITE	10
17	1-0.45-1 BROKEN	WHITE	45
20	SYMBOLS	-	-
] OR [LIMITS OF MARKINGS	-	-

PAVEMENT MARKING DENOTATION:

- 3-3-3, 3-6-3, 3-9-3; LINE-GAP-LINE SPACING IN METRES
- (1) PERMANENT (WATER BORNE)
- (1) DURABLE (THERMOPLASTIC OR COLD PLASTIC)
- (1) EXISTING MARKING TO BE REMOVED

NOTES:

1. ALL MARKINGS SHALL CONFORM WITH THE ONTARIO TRAFFIC MANUAL (OTM), BOOK 11.
2. PROPOSED MARKINGS TO MATCH EXISTING AT ALL WORK AND/OR ROAD RECONSTRUCTION LIMITS.
3. LONGITUDINAL MARKINGS – PAINT ON BASE COURSE. PAINT OR PLASTIC ON TOP COURSE (TO BE DETERMINED BY TRAFFIC GROUP.)
4. TRANSVERSE MARKINGS/SYMBOLS – PLASTIC ON BOTH BASE AND TOP COURSE.

ALL DIMENSIONS IN MILLIMETRES EXCEPT WHERE NOTED



WORKS DEPARTMENT

PAVEMENT MARKING LEGEND

DWG. DATE: 2004 08

REVISION NO.: 4

REV. DATE: 2015 04

SCALE: N.T.S.

S-301.020